

SodaBlast Systems

Complete System Package

200 Flex SodaBlast

OSHA Safety Compliant Pack

Available



www.sodablastsystems.com

Dimensions: 15.5' L x 5.5' W x 5' H 3945 lbs.

System Specifications and Components:

Multi Process System

100 lbs. / 2 cubic foot Multi Media Blaster

Lifetime Factory Warranty

Venturi System

Constant abrasive discharge and positive abrasive control

Manually Set 185 CFM (cu. Ft./min.) @ 150 PSI (lbs./sq.in.)

2 lug Chicago quick coupler for optional safety pack

Easy Access to Quick disconnect air tool operation

In-Line Air Pressure Regulator

0~130 PSI (lbs./sq.in.)

1¼" Body Type

Hard epoxy corrosion protection

High SCFM flow due to efficient aspiration

High Velocity Double Venturi Design Blast Nozzle

4 (¼" bore)

Easy Abrasive Adjustment

Fifty Foot Section of Water Line

Fifty Foot Section of ¾" ID Blast Hose

Swivel Permits 360° Blast Hose Movement

Fill Cap

Fill Funnel

CF-125 Coalescent Filter Dryer

11½" ADC Body

Polycarbonate Bowl

Metal Bowl with Sight Glass

150~220 Pressure PSIG (Mpa)

High Capacity Evaporator Cooling System,

Twelve Volt DC

MT-2 Heavy Duty Air Receiver/Moisture Separator

Lifetime Factory Warranty

Stainless De-Mister ASME Coded Vessel with a manual 3/8" Drain

Forty Nine Horsepower John Deere Diesel Engine

21 Gallon Diesel Tank

Engine Conforms to all applicable California emission regulations

Tier 4 Interim emission standard category

Compliance with 13CCR Section 2424

Compliance with 13CCR Section 2425

and 2426 (emission control system

warranty)

185 CFM 125 PSI Flex Air Sullivan Palatek

Portable Air Compressor

Auxiliary Air Connections for Optional Tool Operations

Two ¾" Service Connection

Oil Level Sight Gauge

Gull Wing Doors for access to components

Noise Level to Maximum of 76dBA at 7 Meters

Automatic Shutdown and Protection System

Standard Instrumentation

Alternator Light

Discharge Pressure Gauge

Hour Meter

Exterior Fluid Drains for:

Diesel Fuel Tank

Engine Oil

Engine Coolant

Compressor Oil

Industrial Grade All Steel Deck Trailer with Electric Brakes

7 Pin Round Connector

2" Trailer Ball

Ground to Level 14½" Center to Ball

Needs Approximately 16" to Level the Trailer

Electric Brakes with Brake Away System

Diamond Plate Floor

12' x 3.75' Work Deck

DOT Compliant



MMLJ, Inc. SodaBlast Systems

5711 Schurmier Rd. Houston, TX 77048

(800) 216-7632 toll free (713) 868-8041 fax

www.sodablastsystems.com

info@sbsllc.com